

EVlink PARKING Floor Standing 22KW 2xT2 with Shutter EV CHARGING STATION

EVF2S22P44

! Discontinued on: 31 Dec 2023

① Discontinued

Main

Range	EVlink	
product name	EVlink parking	
Product or component type	Charging station	
Device short name	EVF2	
Poles description	3P + N for power circuit 1P + N for control circuit	
Mounting mode	Floor-standing	
Offer type	Standard	
rated supply voltage	230 V AC 50/60 Hz control circuit 380415 V AC 50/60 Hz power circuit	
Earthing system	TT TN IT	
socket-outlet number	2	
socket-outlet type	Right: T2 with shutter / silver plated contacts Left: T2 with shutter / silver plated contacts	
Maximum supply current	32 A for T2 with shutter	
Max power	22 kW for T2 with shutter	

Complementary

Control type	2 red push-button, function: stop 2 green illuminated push-button, function: start/unlock flap	
Local signalling	On charge: 2 LED (green) (flashing) on side Available: 2 LED (green) on front Reserved: 2 LED (orange) on front Not operational: 2 LED (red) on front	
Communication port protocol	OCPP 1.6	
Configuration /Architecture	Standalone Clustered architecture	
Operation and maintenance	Load management Circuit breaker status Diagnosis capabilities Charge detail records Postponed charge User privilege configuration	
Web server	Embedded	
Ethernet service	Configuration via web server	

Standards	IEC 61851-22 IEC 61851-1
Product certifications	EV Ready CE ZE Ready CB
Height	1146 mm
Width	413 mm
Depth	220 mm
Net weight	50 kg
Colour	Front: white (RAL 9003) Side: grey (RAL 7016)

Environment

IP degree of protection	IP54 off load conforming to IEC 61851-1 IP54 on load conforming to IEC 61851-1	
IK degree of protection	IK10 charging station conforming to IEC 61851-22 IK10 socket-outlet conforming to IEC 61851-22	
Ambient air temperature for operation	-3050 °C conforming to IEC 61851-22	
Ambient air temperature for storage	-4080 °C	
Operating altitude	02000 m conforming to IEC 61851-22	
Relative humidity	095 %	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	38.0 cm
Package 1 Width	45.0 cm
Package 1 Length	128.0 cm
Package 1 Weight	58.0 kg



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

⊘ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1133
Environmental Disclosure	Product Environmental Profile

Use Better

EU RoHS Directive	Compliant with Exemptions

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information